



750 mm



15 HP



Adjustable Pressure up to 340 kg



3-phase



from 300 to 1300 rpm



REMOTE CONTROL (Optional)

Expander 750

The very best for grinding, honing, polishing and bush-Hammering of large marble, granite, terrazzo and concrete floors! Expander tackles large commercial floors like no other machines before! Its patented planetary system driven not by belts but by tempered-steel gears, sets expander in a league of its own over the competition. Thanks to this exclusive technology, it is the only machine of its kind with an adjustable pressure feature. Nothing is a challenge for expander! It has a powerful 15 or 20 HP motor and works comfortably even in smaller areas. Patented planetary system 750mm (30"). Electric actuator to adjust the working pressure and adjust the elevation of the machine's head.



Electric device to adjust the working pressure



Third Front Wheel

TECHNICAL DATA

Model	Max Power	Drive Inverter	Volt	Grinding Disc Speed rpm	Working Width	Tools	Water Tank	Weight
EXPANDER 750 (15HP)	15 HP	15 kw	3-phase	300-1300	750mm (30")	3x240mm (9,5")	46 lt	340 Kg
EXPANDER 750 HD (15HP)	15 HP	15 kw	3-phase	300-1300	750mm (30")	3x240mm (9,5")	46 lt	340 Kg
EXPANDER 750 HD US (15HP)	15 HP	15 kw	3-phase	300-1300	750mm (30")	3x240mm (9,5")	46 lt	340 Kg



650 mm



10/15 HP



Adjustable Pressure up to 340 kg



3-phase



from 300 to 1300 rpm



REMOTE CONTROL (Optional)

Expander 650

EXPANDER 650, available with 10 or 15 hp motor, owns all the characteristics of EXPANDER 750 version but with a smaller job section (650 mm) and then it is able to work easily even in the tightest spaces.

Key features:

- Ergonomic machine control with 24 Volt push button.
- Sx or Dx rotation.
- Electronically adjustable working pressure.
- Variable speed 300-1300 rpm.
- Third front wheel for easy portability.
- Possibility to work dry or wet system.
- Quick Attack System to change tools.



Electric device to adjust the working pressure



Third Front Wheel

TECHNICAL DATA

Model	Max Power	Drive Inverter	Volt	Grinding Disc Speed rpm	Working Width	Tools	Water Tank	Weight
EXPANDER 650 (10HP)	10 HP	11 kw	3-phase	300-1300	650mm (25,6")	3x240mm (9,5")	46 lt	320 kg
EXPANDER 650 (15HP)	15 HP	11 kw	3-phase	300-1300	650mm (25,6")	3x240mm (9,5")	46 lt	330 kg
EXPANDER 650 US (10HP)	10 HP	11 kw	3-phase	300-1300	650mm (25,6")	3x240mm (9,5")	46 lt	330 kg
EXPANDER 650 US (15HP)	15 HP	11 kw	3-phase	300-1300	650mm (25,6")	3x240mm (9,5")	46 lt	340 kg



530 mm



7 HP



Adjustable Pressure up to 145 kg



3-phase



from 300 to 1300 rpm



Levighetor Max SC 530

Speed Control & Adjustable Pressure

LEVIGHETOR MAX SPEED CONTROL version has the advantages of the VARIABLE SPEED up to 1300 rpm and automatic regulations of working pressure. Ideal for grinding and polishing marble, terrazzo, granite and concrete, floor preparation, bush Hammering, old glues and resins removal, and Superconcrete effect.



TECHNICAL DATA

Model	Max Power	Volt	Grinding Disc Speed rpm	Working Width	Tools	Water Tank	Weight
Levighetor Max VS	7 HP	3-phase	300-1300	530mm (21")	3x240mm (9,5")	18 lt	145 kg