

ROTOKLIN

Rotoklin è una speciale macchina progettata principalmente per:

- Molatura di pavimenti particolarmente dislivellati prima della levigatura con le classiche levigatrici.
- **Rimozione di resine, vernici e colle.** Incredibilmente veloce per questa applicazione.
- Spianare giunti e dislivelli.
- Bocciardatura di pavimenti in cemento e pietra.
- Levigatura e lucidatura di pavimenti.
- **Esposizione degli aggregati.**

ROTOKLIN is a special machine designed mainly for:

- *Grinding particularly uneven floors before Grinding with the classic Grinding machines.*
- **Removal resins, varnishes and glues.**
- *To smooth joints and uneven floors.*
- *Bush-hammering concrete and stone floors.*
- *Grinding and polishing floors.*
- **For fast exposing aggregate.**



| Model | max Power | Volt | Grinding Disc Speed rpm | Working Width | Water Tank | Weight |
|-----------------|-----------|---------|-------------------------|---------------|------------|--------|
| Rotoklin 320 | 4 Hp | 1-phase | 1400 | 320 mm (11") | 18 lt | 77 Kg |
| Rotoklin 400 | 7 Hp | 3-phase | 900 | 400mm (16") | 18 lt | 110 Kg |
| Rotoklin 400 VS | 7 Hp | 3-phase | 700-1400 | 400mm (16") | 18 lt | 120 Kg |



Disco Flottante.
Single floating Grinding Disc.



Manico con Sistema anti-vibrazioni.
Ativibration system handle.



Comandi macchina di facile utilizzo.
Easy to use.



Regolazione automatica della pressione.
Automatic control pressure.



Terza ruota anteriore.
Third front well.

| IMMAGINE / PHOTO | COD. / CODE | DESCRIZIONE / DESCRIPTION |
|------------------|---|---------------------------|
| | BUSH HAMMER ROTOKLIN | |
| | 32030RTK | Bush Hammer plate ø320 |
| | 40030RTK | Bush Hammer plate ø400 |
| | PIATTO PORTA UTENSILE 3 ATTACCHI ø100 AS. Per levigare e lucidare con dischi diamantato ø 100mm AS. <i>To use diamond with AS attach ø 100mm.</i> | |
| | UT34703 | ø 320mm |
| | UT340901 | ø 400mm |
| | SKRAPER RING ø400mm (WITH 6 SKRAPERS) | |
| | 70091 | SKRAPER 400 |
| SERIES DT | UTENSILI DIAMANTATI STANDARD PER LA MOLATURA E PREPARAZIONE DEL CLS Non usare su pavimenti abrasivi. Ideali per un ottima resa e riduzione dei costi. STANDARD DIAMOND TOOLS FOR GRINDING AND FLOOR PREPARATION Do not use on abrasive floors. Designed for effective, efficient grinding, Achieve maximum square footage at minimum cost | |
| | DT ø320 (12 Segments) | |
| | 320819DT12S | DT00 grit.20 ø320 |
| | 320820DT12S | DT0 grit.40 ø320 |
| | 320821DT12S | DT1 grit.70 ø320 |
| | 320822DT12S | DT2 grit.140 ø320 |
| | DT ø400 (16 Segments) | |
| | 400819DT16S | DT00 grit.20 ø400 |
| | 400820DT16S | DT0 grit.40 ø400 |
| | 400821DT16S | DT1 grit.70 ø400 |
| 400822DT16S | DT2 grit.140 ø400 | |
| SERIES CA | UTENSILI DIAMANTATI PREMIUM QUALITY PER CEMENTI ABRASIVI E ASFALTO. PREMIUM QUALITY DIAMOND TOOLS FOR ABRASIVE CONCRETE AND ASPHALT. | |
| | CA ø320 (12 Segments) | |
| | 320819CA12S | CA00 grit.20 ø320 |
| | 320820CA12S | CA0 grit.40 ø320 |
| | 320821CA12S | CA1 grit.70 ø320 |
| | 320822CA12S | CA2 grit.140 ø320 |
| | CA ø400 (16 Segments) | |
| | 400819CA16S | CA00 grit.20 ø400 |
| | 400820CA16S | CA0 grit.40 ø400 |
| | 400821CA16S | CA1 grit.70 ø400 |
| | 400822CA16S | CA2 grit.140 ø400 |

GRINDING

SINGLE DISC

TOOLS

SPECIAL

VACUUM

CHEMICALS

FRIENDLY